

## IMAGE SENSING APPARATUS

### BACKGROUND OF THE INVENTION

#### Field of the Invention

5           The present invention relates to image sensing apparatus for sensing an image of an object and a method of controlling the image sensing apparatus.

#### Related Background Art

10           It is known that, when fluorescent substances of certain kinds are exposed to radiations (X-rays,  $\alpha$ -rays,  $\beta$ -rays,  $\gamma$ -rays, electron beams, ultraviolet rays, etc.), part of the radiation energy is accumulated in the fluorescent substances and that, when such  
15           fluorescent substances are then exposed to scintillation light such as visible light or the like, the fluorescent substances exhibit stimulated emission according to the accumulated energy. The fluorescent substances possessing this property are called storage type phosphors (photostimulable phosphors).

20           There are proposals of radiographic information recording/reproducing systems making use of such storage type phosphors and configured to record radiographic image information of an object such as a human body or the like once in a sheet of an storage  
25           type phosphor, scan this storage type fluorescent sheet with scintillation light such as laser light or the like to cause stimulated emission, then

090242-08001

5

10

25

the power is also turned on for such devices as an X-ray film changer, an X-ray solid-state imaging device, and so on, thereafter the power is kept on during hours when objects, e.g., patients can appear, and the power is turned off after an end of the last image sensing in that day.

It is very rare for the image sensing apparatus to sense X-rays incessantly during the hours. It is thus common practice to control the sensing apparatus to low power consumption during non-sensing periods or to bring the system into a standby mode in which the imaging device is liberated from an imaging state so as to reduce the load on the imaging device. For implementing it, for example, an operator provides a command to transfer the system into the standby mode, or the sensing apparatus automatically moves into the standby mode if there is no access to the sensing apparatus for a predetermined period.

When an object, e.g., a patient appears, the apparatus normally shifts from the standby mode into the normal imaging mode in response to a command inputted by the operator.

Japanese Laid-Open Patent Application No. 10-104766 discloses the prior art in which a patient detecting sensor is provided in proximity to the X-ray image sensor, the X-ray image sensor is kept in the sensing state (on) only during a period when a patient

05923422-080801

is present in front of the sensor, and the sensor is turned into the standby state (off) during periods when no patient is present.

Since the conventional apparatus makes transitions  
5 between the sensing mode and the standby mode according to instructions from the operator, as described above, the apparatus can be maintained in a state of preparation for sensing in spite of absence of a human body (object) because of an operation error of the  
10 operator, a long setting of the predetermined period, or the like. This can sometimes result in decreasing the lifetime of the X-ray sensing device. Sensors comprised of semiconductors can suffer problems of occurrence of a wait time during the preparation for  
15 sensing or before sensing, and decrease in the total product life. Energization of the sensing part for a long period will result in generating excess heat in the sensor housing and the heat can bring about a demerit of increasing offsets of the sensor or a read-  
20 out circuit.

#### SUMMARY OF THE INVENTION

An object of the present invention is to provide an image sensing apparatus with a long lifetime and a  
25 method of controlling the image sensing apparatus.

Another object of the present invention is to provide an image sensing apparatus that can sense an

0992422-080801

image with reduced noise and a method of controlling the image sensing apparatus.

In order to accomplish the above objects, according to one aspect of the present invention, there is provided an image sensing apparatus comprising:

a sensor region including a plurality of pixels for detecting an image of an object;

a read-out circuit adapted to sequentially read out signals from the plurality of pixels into a common output portion; and

a power supply unit adapted to supply electric powers to the sensor region and to the read-out circuit independently.

According to another aspect of the present invention, there is provided a method of controlling an image sensing apparatus comprising a sensor region including a plurality of photoelectric conversion elements for detecting an image of an object and a read-out circuit adapted to sequentially read out signals from the plurality of photoelectric conversion elements into a common output portion, the method comprising:

a step of supplying electric powers to the sensor region and to the read-out circuit independently.

The other objects and features of the present invention will become apparent from the description of the specification and drawings which will follow.

05923422-080801

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a diagram showing a detailed configuration of an X-ray image sensing apparatus;

Fig. 2 is an equivalent circuit diagram of a sensor;

Fig. 3 is a circuit diagram of a flat sensor panel;

Fig. 4 is a diagram showing power on timing generating parts;

Fig. 5 is a diagram showing a first power on timing example;

Fig. 6 is a diagram showing a second power on timing example; and

Fig. 7 is a diagram showing a third power on timing example.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

The embodiments of the present invention will be described below with reference to the drawings.

In order to lengthen a lifetime of a flat panel sensor (sensor) comprised of semiconductors, the image sensing apparatus according to an embodiment of the present invention is configured to supply the electric power to the flat panel sensor and the electric power to the read-out circuit including amplifiers for amplifying electric signals from the sensor, a multiplexer for sequentially reading out signals from

Describing the above in more detail, the flat panel sensor has the feature of small power consumption and thus poses no problem in terms of heat generation, but, when image sensing is started immediately after turning-on of power, the sensor shows high offset amounts of respective channels and fails to obtain a stable image. In order to solve it, it can be contemplated that the power to the sensor is turned on at the timing of the detection of a signal from a patient detecting sensor or order information from a radiation information system and the power to the sensor is turned off at the timing of the detection of absence of a patient or at the time of completion of sequential image sensing. In the strict sense, however, in view of the fact that the lifetime of the sensor is decreased by supplying power to the sensor, it is desirable to turn the power to the sensor on not during the period when the patient is present in front of the sensor but the period of sensing.

25        However, offsets are relatively large if the power  
to the sensor is turned on immediately before X-ray  
exposure. This can be solved in such a way that the  
operator provides a request for actuation of an X-ray

However, the time from the ready request signal to the ready signal, which is dependent on the X-ray generator, can be conceivably insufficient for the stability of offsets, depending upon characteristics of the sensor. In this case, an exposure permission signal to the X-ray generator can be generated after a lapse of a predetermined period since turning-on of power to the sensor in response to the ready request signal. As another means, it is also possible to check offset amounts of the sensor panel in real time by use

However, the time from the ready request signal to the ready signal, which is dependent on the X-ray generator, can be conceivably insufficient for the stability of offsets, depending upon characteristics of the sensor. In this case, an exposure permission signal to the X-ray generator can be generated after a lapse of a predetermined period since turning-on of power to the sensor in response to the ready request signal. As another means, it is also possible to check offset amounts of the sensor panel in real time by use



of the read-out circuit and generate the exposure permission signal while monitoring the offset amounts, though control is very complex. In this case, it is necessary to turn on an electric power of the read-out circuit on the occasion of reading the offsets.

On the other hand, since the read-out circuit for reading out data from the sensor comprises amplifier circuit which is power-consuming, it generates heat during long-term operation and the heat can adversely affect the sensor or the read-out circuit. Since the read-out circuit can operate stably even immediately after turning-on of power, it is appropriate to use either of two power- on timings. One is an exposure request signal (a signal generated in response to an X-ray exposure request from the operator or the like), and the other an X-ray exposure completion signal. The exposure completion signal can be generated based on an off signal of high voltage of the X-ray generator, or a sensor for monitoring X-rays may be provided on the image sensing apparatus side to be used for the generation of the exposure completion signal.

Referring to Fig. 1, the entire X-ray image sensing system (image sensing apparatus) of the present embodiment will be described. Numeral 101 designates an X-ray room, 102 an X-ray control room, and 103 a diagnostic room. The overall operation of the present X-ray image sensing system is controlled by a system

control unit 110. The functions of the system control unit 110 are mainly those described below.

The system control unit 110 first receives an instruction from the operator through an operator interface 111. The image acquisition is implemented using an X-ray control console 501 in addition to the operator interface 111.

The operator interface 111 can be either of a touch panel on a display, a mouse, a keyboard, a joy stick, a foot switch, and so on. Using the operator interface 111 the operator can set imaging sensing conditions (still picture, motion picture, X-ray tube voltage, tube current, X-ray exposure time, etc.), image sensing timing, image processing conditions, subject ID, a method of processing a captured image, and so on, but the operator does not have to input them one by one, because almost all information is transferred from a radiation information system. An operator's important task is a work of confirming a sensed image. Namely, the operator makes judgments about whether the angle is correct, whether the patient is freezed, whether the image processing is appropriate, and so on.

Then the system control unit 110 provides an instruction of image sensing conditions based on the instruction from the operator 105, to a sensing control unit 214 in charge of the X-ray sensing sequence and

09923422-030304

5

10

15

20

25

based on an instruction from the sensing control unit 214. The X-ray beam 125 is transmitted by the subject 126 and the image sensing bed 130 to impinge on the X-ray detector 140 thereafter.

5           The X-ray detector 140 is comprised of a grid 141, a scintillator 142, a sensor 8, an X-ray exposure dose monitor (AEC) 144, and a driving circuit 145. Here the driving circuit includes the read-out circuit for reading signals from the sensor and a line selector for  
10       selecting pixels to be read out in the sensor. The grid 141 reduces influence of X-ray scattering caused by the transmission through the subject 126. The grid 141 consists of an X-ray low absorbing member and an X-ray high absorbing member and is, for example, of a  
15       stripe structure of Al and Pb. During X-ray irradiation the grid 141 is moved based on an instruction from the sensing control unit 214 in order to avoid occurrence of a moire pattern because of the frequency difference between the photosensor array 8  
20       and the grid 141.

          In the scintillator 142 a matrix substance of a fluorescent material is excited by X-rays having high energy to emit fluorescence in the visible region based on recombination energy upon recombination. The  
25       fluorescence is one originating in the matrix itself, such as  $\text{CaWO}_4$  or  $\text{CdWO}_4$ , or one originating in a luminescence center substance activated in the matrix,

such as CsI:Tl or ZnS:Ag.

The sensor 8 for detecting the object image is placed adjacent to this scintillator 142. This sensor 8 converts photons to electric signals. The X-ray exposure dose monitor 144 senses the amount of transmitted X-rays. The X-ray exposure dose monitor 144 may be one directly detecting X-rays by a crystalline silicon photodetector or the like, one of an ion chamber type placed in front of the sensor 8, or one detecting light from the scintillator 142.

In this example, the sensor detects visible light (proportional to the amount of X-rays) transmitted by the scintillator and sends the information to the sensing control unit 214, and the sensing control unit 214 drives the high-voltage generating power source 124, based on the information, to shut off or control X-rays. The driving circuit 145, including the read-out circuit for reading the data from the sensor 8, and others, drives the flat panel sensor 8 under control of the sensing control unit 214 to read out signals from the respective pixels. The sensor 8 and driving circuit 145 will be detailed later.

The image signals from the X-ray detection unit 140 are transferred from the X-ray room 101 to the image processing unit 10 in the X-ray control room 102. Since noise due to generation of X-rays is high in the X-ray room 101, the image data cannot be transferred

09523426-080801

accurately because of the noise in certain cases.  
Therefore, the transfer line needs to be provided with  
high noise resistance. It is thus desirable to employ  
a transmission system provided with an error correction  
5 function and, in addition thereto, to use a  
transmission line constructed of a shielded, twisted  
pair cable or an optical fiber with a differential  
driver, for example. In the image processing unit 10,  
display data is switched based on an instruction from  
10 the sensing control unit 214 (which will be detailed  
later). In addition to these, it is also possible to  
implement correction for image data, spatial filtering,  
recursive processing, etc. in real time or to implement  
tone processing, correction for scattered radiation, DR  
15 compression processing, and so on.

The image thus processed is displayed through a  
display adapter 151 on a display unit 160. At the same  
time as the real-time image processing, the basic  
image, after subjected to only the correction for data,  
20 is saved in a fast memory 161. The fast memory 161 is  
desirably a data storage device satisfying large  
capacity, high speed, and high reliability and  
desirably, for example, a hard disk array or the like  
such as RAID or the like. Based on an operator's  
25 instruction, the image data saved in the fast memory  
161 is stored in the external memory. On that  
occasion, the image data is reconstructed so as to

090342-080801

5

10

25

coupled device) or a photomultiplier tube. In the case of such another device, the A/D conversion unit can be constructed with similar function and in similar structure.

5           Now description will be given referring back to Fig. 2. In the present embodiment one pixel 1 is comprised of a photoelectric conversion element 21 and a switching TFT (thin-film transistor) 22 for controlling storage and reading of charge, and is  
10           generally made of amorphous silicon ( $\alpha$ -Si) formed on a glass substrate. The photoelectric conversion element 21 may be constructed of simply a photodiode 21D having a parasitic capacitance, or a configuration including the photodiode 21D and an additional capacitor 21C to  
15           improve the dynamic range, which are connected in parallel.

          The anode A of the diode 21D is connected to a bias wire Lb which is a common electrode, and the cathode K thereof is connected to the controllable  
20           switching TFT 22 for reading out the charge stored in the capacitor 21C. In this example, the switching TFT 22 is a thin-film transistor connected between the cathode K of the diode 21D and a charge reading amplifier 26.

25           A signal charge appears in such a manner that the capacitor 21C is first reset by operation of the switching TFT 22 and a reset switching device 25,

04923422-080801



thereafter radiations 1 are emitted, the photodiode 21D generates a charge according to a dose of radiations, and the charge is accumulated in the capacitor 21C. After that, the signal charge is again transferred to a capacitative element by operation of the switching TFT 22 and the reset switching device 25. Then the amount of the charge stored by the photodiode 21D is read out as a potential signal by the preamplifier 26 and the signal is subjected to A/D conversion to detect the dose of incident radiations.

Fig. 3 is an equivalent circuit diagram showing a photoelectric conversion apparatus including the sensor 8 and the driving circuit 145 (the read-out circuit 36 and the line selector 32). The photoelectric conversion operation will be described below in a specific expanded configuration in which a plurality of photoelectric conversion elements of the structure shown in Fig. 2 are arrayed two-dimensionally.

The sensor 8 is composed of a pixel array of approximately  $2000 \times 2000 - 4000 \times 4000$  pixels and the array area is approximately  $200 \text{ mm} \times 200 \text{ mm} - 500 \text{ mm} \times 500 \text{ mm}$ . In Fig. 3, the photodetector array 8 is composed of  $4096 \times 4096$  pixels and the array area is  $430 \text{ mm} \times 430 \text{ mm}$ . Therefore, the size of each pixel is approximately  $105 \text{ } \mu\text{m} \times 105 \text{ } \mu\text{m}$ . 4096 pixels in one block are wired laterally and 4096 lines are arranged vertically in order, thereby two-dimensionally

092342-080301

The above example was the example in which the sensor 8 of  $4096 \times 4096$  pixels was constructed of one substrate, but it is also possible to construct the sensor 8 of  $4096 \times 4096$  pixels of four sensors each having  $2048 \times 2048$  pixels. When the single sensor 8 is constructed of four detectors of  $2048 \times 2048$  pixels, this configuration presents the merit of improvement in yields because of fabrication of divided detectors.

The K electrodes of the respective photoelectric conversion elements 21 (m, n) in each column of the sensor 8 are connected through the source and drain conductive paths of the corresponding switching TFTs 22 (m, n) to a common column signal line (Lc1 to Lc4096) corresponding to each column.

For example, the photoelectric conversion elements 21 (1,1) to 21 (1,4096) of column 1 are connected to a first column signal line Lc1. The A electrodes of the

5

10

20

25

38. The analog multiplexer 39 sequentially outputs the output signals to the A/D converter 40 to convert them to digital values and the digital signals are transferred to the image processing unit 10.

5           The photoelectric conversion apparatus of the present embodiment is configured to separate the  $4096 \times 4096$  pixels into the 4096 lines Lcn, simultaneously transfer outputs of 4096 pixels per row, and sequentially output the signals through the column  
10   signal lines Lc and through the 4096 preamplifiers 26 and 4096 sample hold circuits 38 to the A/D converter 40 by the analog multiplexer 39.

          In Fig. 3 the A/D converter 40 appears as if it were constructed of a single converter, but the A/D  
15   converter unit in practice is comprised of 4 to 32 systems of A/D converters 40 to execute A/D conversion simultaneously. Namely, signals from every plural columns are supplied to a common A/D converter. The reason is that the read-out time of image signals is  
20   required to be shortened without unnecessary increase of the analog signal band and A/D conversion rates. The A/D conversion unit will be detailed later.

          The accumulation time and the A/D conversion time are in an intimate relation and fast A/D conversion  
25   will result in broadening the band of the analog circuit, which makes it difficult to achieve a desired S/N ratio. Therefore, the read-out time of image

092342-080301  
T08080-24E2560

5       Therefore, an appropriate number needs to be selected  
in consideration of the above-stated points.

For example, in order to capture the image in 100 msec by sequentially driving all the pixels, the analog signal band is approximately 50 MHz and the A/D conversion is carried out, for example, at the sampling rate of 10 MHz, which requires at least four systems of A/D converters 40. In the present image sensing apparatus the A/D conversion is executed simultaneously by sixteen systems. Output signals from the sixteen systems of A/D converters 40 are supplied to sixteen systems of respectively corresponding memories not shown (FIFOs or the like). The memories are selectively switched to gain image data for one continuous scan line, and the image data is transferred to the subsequent image processing unit 10, or to a memory thereof. After this, the image data is displayed as an image or as a graph on a monitor such

as a display unit.

ON/OFF cycles of power of the conventional X-ray image sensing apparatus are normally power cycles of one-day periodicity, but power ON/OFF timing of the image sensing apparatus of this embodiment is as follows.

Fig. 4 shows constitutive portions necessary for turning-on of electric powers to the sensor 8 and to the read-out circuit 36. The X-ray control table 501 has at least two switches of X-ray ready request switch (SW) 601 for output of an X-ray ready request signal and an X-ray exposure request SW 602 for output of an X-ray exposure request signal, and is connected to the high voltage generation device 124, to the AEC 144, and to the sensing control unit 214. The sensing control unit 214 has an exposure permission timer 603 and is connected to the AEC 144, to the electric power source 502 of the sensor, and to the electric power source 503 of the read-out circuit.

When the operator pushes the X-ray ready request SW 601, the X-ray ready request signal is generated. In response to this signal the X-ray device initiates the preparation for exposure, e.g., rotation of the rotary anode of the tube. In general, the operator often also depresses the X-ray exposure request SW 602 at the same time as the depression of the X-ray ready request SW 601. In this case, when the rotary anode of

the tube reaches constant rotation to become ready for X-ray exposure, and then after the device becomes ready for X-ray exposure, the X-ray exposure request signal is asserted and X-ray exposure starts.

5           First presented in Fig. 5 is a first timing example showing a relation among the exposure timing of the X-ray generator and the supply timings of powers to the sensor 8 and to the read-out circuit 36.

10           The sensor power source 502 is turned on with the timing of output of the X-ray ready request signal and the read-out circuit power source 503 is turned on with the timing of output of the exposure request signal. When the X-ray exposure device (AEC) 144 then detects X-rays amount enough for sensing, the AEC 144 shuts off  
15           the X-ray exposure. Then the control unit starts reading out data and then turns off the two power sources (the sensor power source 502 and the reading-out drive circuit power source 503) at the time of completion of read-out. The above operation is the  
20           first timing example which is controlled by the sensing control unit 214.

25           Next presented is a second timing example showing a relation among the exposure timing of the X-ray generator and the supply timings of powers to the sensor 8 and the read-out circuit 36.

          The second example is an example in which the read-out circuit power source 503 is turned on based on

0923422-080801

the X-ray exposure completion signal and is shown in Fig. 6. The advantage of this example is the merit of capability of minimizing the ON time of the read-out circuit which causes large power dissipation. For transmission of an exposure completion signal, it is conceivable to directly connect the signal of the AEC 144 to the sensing control unit 214 as shown in Fig. 4, or to utilize a signal of a circuit (which is not shown in the drawings) monitoring the high voltage of the high voltage generation device 124. Use of the signal monitoring the high voltage enables X-rays corresponding to a delay of shut-off of X-rays to be accurately integrated as well. The completion of exposure may also be detected in such a manner that an X-ray monitor (which is not shown in the drawings) different from the AEC 144 is provided, for example, on the back side of the sensor 8, though not shown, to monitor the X-rays exposure, and completion of exposure is determined by use of a signal from the monitor.

Next presented is a third timing example showing a relation among the exposure timing of the X-ray generator and the supply timings of powers to the sensor 8 and to the read-out circuit 36.

The third timing example is presented in Fig. 7. The third timing example is different from the second example in that the exposure request signal is not outputted without output of exposure permission from

090342250



the sensor. The first and second examples were arranged so that if the exposure request SW 602 was depressed and if the system was ready for X-ray exposure, then the exposure request signal was asserted to start the X-ray exposure, whereas the third example is arranged so that, in order to ensure a sufficient time after turning-on of the sensor power source 502 for the photodetection array 8, the sensing control unit 214 is provided with the exposure permission timer 603 (Fig. 4), a permission signal is not outputted unless a fixed time for stabilization of sensor offsets has elapsed since turning-on of the sensor power source 502, and after assertion of this permission signal, the exposure request signal is then asserted. The set time of the exposure permission timer 603 is determined in consideration of the characteristics of the sensor used and is set, for example, upon shipment from a factory, or upon installation at an installation site.

How each of the circuit components in the sensor 8 and in the read-out circuit 36 is turned on or off will be described below with reference to Table 1 and Fig. 3.

As summarized in the table below, all the circuits in the sensor 8 and in the read-out circuit 36 are in a state of Phase 1 in which no electric power is supplied thereto, before the sensing request. When the X-ray Ready-Request signal is outputted based on the sensing

request from the radiation information system (RIS/HIS) or based on the sensing request from the operator, the circuits move into Phase 2 with detection of the signal. In Phase 2, the power is supplied to the bias power line Lb, the row select lines Lr, and the column select lines Lc of the sensor 8. Describing it referring to Fig. 3, the power is supplied to the circuits shown below the preamplifiers 26. When the X-ray exposure request signal is detected in the state of Phase 2, when completion of actual exposure is detected, when turning of the high voltage generation device into Low is detected, or when a time-out of the integration control circuit occurs, the power is supplied to all the circuits shown in Fig. 3. Namely, the power is also additionally supplied to the preamplifiers 26, the sample hold circuits 28, the multiplexer 38, and the A/D converter 40. When in a state of Phase 3, all charges undergo A/D conversion and then completion of read-out is detected, the circuits transfer into Phase 4. In Phase 4, it is determined whether subsequent sensing is to be carried out. The circuits go into Phase 2 if yes, or into Phase 1 if no.

In the description provided above, it is described that the preamplifiers 26 and the sample hold circuit 28 are in an off-state in the Phase 2. However, it may also possible in the Phase 2 that they are in an on-



read-out circuit are kept in a standby state (which was described above by the term "power OFF") with no voltage being applied to each of them.

Describing the standby state of the sensor specifically, it can be contemplated that all the drive lines Lc, Lr, Lb of the sensor 8 are set at an identical potential, e.g., at the GND potential so as to apply no voltage to the sensor 8. As for the standby of the read-out circuit 36, it can be contemplated that the standby is implemented by turning off power of each of the preamplifiers 26, the sample hold circuit 38, the multiplexer 39 and the A/D converter 40 in a state in which potentials of the peripheral line selector 32, the read-out circuit 36 and the power source 31 are set to a same potential.

It can also be contemplated that, without supplying the two power sources for the sensor and for the read-out circuit, there is provided only one common power source and then the power is supplied to the both or to either one of them by switching.

When the amount of heat generated by the drive read-out circuit is small, it can also be contemplated that the sensor power source 502 and the drive power source 503 are turned on on the basis of the X-ray ready request signal. In this case the technological advantages can be also achieved as compared with the prior art examples.

TOP SECRET

As described above, the power source system of the sensing part or the power supply system is separated into those for the sensor and for the read-out circuit and these are turned on or off in accordance with the X-ray exposure timing and the time for stabilization of the sensor, which can lengthen the lifetime of the sensor. The power consumption is reduced, so as to suppress generation of heat and thereby decrease the offsets of the sensor due to the heat, whereby the image sensing apparatus can be obtained with less noise in the image.

The present invention also embraces in its scope such configurations that program code of software for implementing the functions of the above embodiments is supplied and the system is operated according to the program stored in a computer (CPU or MPU) of the image sensing apparatus to carry out the functions.

In this case, the program code itself of the above software implements the foregoing functions of the embodiments and thus the program code itself and the means for supplying the program code to the computer, e.g., a recording medium storing the program code, constitute the present invention. The recording medium storing the program code can be selected, for example, from a floppy disk, a hard disk, an optical disk, a magnetooptical disk, a CD-ROM, a magnetic tape, a nonvolatile memory card, a ROM, and so on.

The above embodiments represent only some of embodied forms for carrying out the present invention, but it is to be understood that the technical scope of the present invention is by no means limited to these  
5 examples. Namely, the present invention can be carried out in various forms without departing from its technical concept or from the principal features thereof.

According to the embodiments of the invention, as  
10 described above, it becomes feasible to make the timing of supply of the power to the sensor 8 different from the supply timing of the power to the read-out circuit 36, which can lengthen the lifetime of the sensor. The power consumption is reduced, so as to suppress  
15 generation of heat, whereby the image can be obtained with less noise.

0923422-080807  
TOP SECRET